

Concrete Pave Stones
Cobble-Stone



PAVESTONE®



**IMPROVING
YOUR
LANDSCAPE™**

Cobble-Stone

Imparting classic, European elegance to paved areas with its old world design, Cobble-Stone offers unique design possibilities. With rounded edges, the natural stone look is available in rectangular and square pave stones. Cobble-Stone can be used in various combinations for an array of exciting pattern designs.

APPLICATIONS

Urban Street Paving • Entrance Areas • Porte-Cocheres • Crosswalks
Esplanades • Light Duty Parking Lots • Residential Driveways
Patios • Walkways • Pedestrian Malls • Medians Terraces • Pool
Decks • Sidewalks • Garden Paths • Roof Gardens

COMPOSITION AND MANUFACTURE

Cobble-Stone is made from a "no slump" concrete mix. Made under extreme pressure and high frequency vibrations, Cobble-Stone has an average compressive strength greater than 8000psi, a water absorption maximum of 5% and will meet or exceed ASTM C-936 and freeze-thaw testing per section 8 of ASTM C-67.


INSTALLATION

1. Excavate unsuitable, unstable or unconsolidated subgrade material and compact the area which has been cleared. Backfill and level with dense graded aggregate suitable for base material (typically 4-6 in. of compacted base for light vehicular and pedestrian traffic) or as otherwise directed by Site Engineer/Architect/Landscape Architect.
2. Place bedding course of washed sand conforming to the grading requirements of ASTM C-33 to a maximum uniform depth of 1-1 1/2 in. (25-38mm) screeded to the grade and profile required.
3. Install Cobble-Stone with joints approximately 1/8 in. (3mm).
4. Where required, cut pavers with an approved cutting device to fit accurately, neatly and without damaged edges.
5. Tamp pavers with a plate compactor, uniformly level, true to grade and free of movement.
6. Spread sand to 1/8 in. (3 mm) thickness over entire paving area.
7. Make one more pass with plate compactor to fill joints with sand.


Complete installation & specification details are available by contacting your Pavestone Sales Representative.

Note: Colors are shown as accurately as possible in brochures & samples, but due to the nature of the product, regional color differences and variables in print reproduction, colors may not match exactly. For best results in maintaining color consistency, pavers must be installed from several cubes at a time. Efflorescence, a whitish, powder-like deposit, may appear on concrete pavers. This is a natural occurrence in any concrete product and will usually wear off over time.

INSTALLATION PATTERNS



Random Runner
Bond



Random Mosaic

PRODUCT INFORMATION

Cobble-Stone is available in six (6) sizes. Height/Thickness 2 3/8" = 60mm



1/2 Square
(Twinkie)



Rectangle



Square



3/4 Square
(Giant Twinkie)



Giant Rectangle



Giant Square

BUNDLED INDIVIDUALLY

Cobble-Stone II Rectangle

4 1/2 W x 6 13/16" L
115mm x 172mm x 60mm
Wt./Stone: 6 lbs.
Stones/Pallet: 490
Approx. Wt./Pallet : 2,884 lbs.
Sq.ft./Pallet: 103
Product Number: 437

Cobble-Stone III Square

4 1/2 W x 4 1/2" L
115mm x 115mm x 60mm
Wt./Stone: 4 lbs.
Stones/Pallet: 700
Approx. Wt./Pallet : 2,800 lbs.
Sq.ft./Pallet: 100
Product Number: 426

*Cobble-Stone IV 3/4 Square

3 3/8 W x 4 1/2" L
86mm x 115mm x 60mm
Wt./Stone: 3.08 lbs.
Stones/Pallet: 900
Approx. Wt./Pallet : 2,772 lbs.
Sq.ft./Pallet: 99
Product Number: 477

Cobble-Stone V Giant Rectangle

6 13/16 W x 10 1/8" L
172mm x 258mm x 60mm
Wt./Stone: 13.44 lbs.
Stones/Pallet: 200
Approx. Wt./Pallet : 2,688 lbs.
Sq.ft./Pallet: 96
Product Number: 456

Cobble-Stone VI Giant Square

6 13/16 W x 6 13/16" L
172mm x 172mm x 60mm
Wt./Stone: 9 lbs.
Stones/Pallet: 350
Approx. Wt./Pallet : 3,150 lbs.
Sq.ft./Pallet: 113
Product Number: 424

*Requires minimum quantity.
Call your local Pavestone
facility for details.

Cobble-Stone I

Cobble-Stone 1/2 Square

2 1/4 W x 4 1/2" L
57mm x 115mm x 60mm
Wt./Stone: 2 lbs.
Stones/Pallet: 200

Cobble-Stone Square

4 1/2 W x 4 1/2" L
115mm x 115mm x 60mm
Wt./Stone: 4 lbs.
Stones/Pallet: 600

Approx. Total Weight/Pallet = 2,800 lbs.

Total Sq.ft./Pallet = 100

Product Number: 447

Cobble-Stone 3-Way

Cobble-Stone 1/2 Square

2 1/4 W x 4 1/2" L
57mm x 115mm x 60mm
Wt./Stone: 2 lbs.
Stones/Pallet: 90

Cobble-Stone Square

4 1/2 W x 4 1/2" L
115mm x 115mm x 60mm
Wt./Stone: 4 lbs.
Stones/Pallet: 270

Cobble-Stone Rectangle



4 1/2 W x 6 13/16" L
115mm x 172mm x 60mm
Wt./Stone: 6 lbs.
Stones/Pallet: 240

Approx. Total Weight/Pallet = 2,744 lbs.

Total Sq.ft./Pallet = 98

Product Number: 423

Typical Cross Section Of Concrete Paver Installation



PAVESTONE[®]
Improving Your Landscape[™]

www.pavestone.com

- Atlanta, GA: (770) 306-9691
- Austin/San Antonio, TX: (512) 558-7283
- Boston, MA: (508) 947-6001
- Charlotte, NC: (704) 588-4747
- Cincinnati, OH: (513) 474-3783
- Colorado Springs, CO: (719) 322-0101
- Dallas/Ft. Worth, TX: (817) 481-5802
- Denver, CO: (303) 287-3700
- Hagerstown, MD: (240) 420-3780
- Houston, TX: (281) 391-7283
- Kansas City, MO: (816) 524-9900
- Las Vegas, NV: (702) 221-2700
- New Orleans, LA: (985) 882-9111
- Phoenix, AZ: (602) 257-4588
- Sacramento, CA: (916) 452-5233
- St. Louis/ Cape Girardeau, MO: (573) 332-8312
- Winters, CA: (530) 795-4400

